




Dimension :
Unit in mm




PRODUCT SPECIFICATION

Model	Driver	Dimension (ØD x H)	Beam Angle	CCT	CRI	Power	Lumen	Casing Colour
SRDL2-4-10W	LiFUD / Osram / Philips	Ø 130 x 100 mm	90°	3000K / 4000K / 6000K	80 / 90	10W	900	White / Black
SRDL2-6-15W		Ø 165 x 115 mm				15W	1350	
SRDL2-6-20W		Ø 165 x 115 mm				20W	1800	
SRDL2-8-30W		Ø 200 x 130 mm				30W	2700	

8" can modify to Emergency Lighting

Photometric



Features :

- * High Power Factor > 0.9
- * THD < 20
- * Life Time >50000Hrs
- * High Lumen Output
- * Low Power Consumption
- * Non Dimmable
- * 1-10v Dimming
- * Dali Dimming
- * Safety Cert IEC/EN 61347
- * Sirim approved
- * Emergency lighting

Application:

- * Office
- * Shopping mall
- * Commercial Building
- * School
- * Residentials

Material :

- * Die-Cast Aluminium
- * Opal Diffuse Len

DONE **LiFUD** **PHILIPS** **OSRAM**



* We maintains a tolerance of ±10% on flux and power measurements